Application No.: NEW Docket No.: 0020-5484PUS1

AMENDMENTS TO THE CLAIMS

1. (Original) A composite papyraceous material, comprising a fibrous polytetrafluoroethylene and a fibrous polytmide.

- 2. (Original) The composite papyraceous material according to Claim 1, wherein the fibrous polyimide is a crystalline fiber.
- 3. (Currently amended) The composite papyraceous material according to Claim 1 or 2, wherein the polyimide is thermoplastic.
- 4. (Currently amended) The composite papyraceous material according to any one of Claims 1 to 3 Claim 1, wherein the polyimide is a polyimide represented by the following Chemical Formula (1):

wherein R represents a quadrivalent aromatic residue selected from monocyclic aromatic groups, condensed polycyclic aromatic groups, and uncondensed polycyclic aromatic groups in which the aromatic rings are bound to each other directly or via a crosslinking group; X represents a direct bond or a bivalent residue selected from hydrocarbon groups, a carbonyl group, an ether group, a thio group or a sulfonyl group; and Y_1 to Y_4 respectively represent a hydrogen or halogen atom or a monovalent residue selected from an alkyl group or an alkoxyl group.

5. (Currently amended) The composite papyraceous material according to any one of Claims 1 to 4 Claim 1, wherein the polyimide is a polyimide represented by the following Chemical Formula (2):

2 ADM/smt

$$\begin{array}{c|c} & & & & \\ & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & \\ & & & \\ & & & \\ & & & \\ & & & \\$$

- 6. (Currently amended) The composite papyraceous material according to any one of Claims 1 to 5 Claim 1, wherein the fibrous polyimide is a short fiber having an average fiber diameter of 3 to 30 μ m and an average fiber length of 1 to 15 mm.
- 7. (Currently amended) The composite papyraceous material according to any one of Claims 1 to 6 Claim 1, wherein the fibrous polytetrafluoroethylene is a fibrous powder that has an average fiber length of 100 to 5,000 μ m and an average shape factor of 5 or more.
- 8. (Currently amended) The composite papyraceous material according to any one of Claims 1 to 7 Claim 1, wherein the polytetrafluoroethylene has a low temperature-sided peak area ratio of 88.5% or more with respect to the total peak area, as determined from the melting endothermic curve obtained at a heating rate of 5°C per minute in differential scanning calorimetry analysis.
- 9. (Currently amended) The composite papyraceous material according to any one of Claims 1 to 8 Claim 1, wherein the fibrous polytetrafluoroethylene is thermally fused and bonded to the fibrous polyimide.
- 10. (Currently amended) A method for producing the composite papyraceous material according to any one of Claims 1 to 8 Claim 1, wherein the composite papyraceous material is prepared from the fibrous polytetrafluoroethylene and the polyimide by a papermaking method.

3 ADM/smt

Application No.: NEW Docket No.: 0020-5484PUS1

11. (Original) The method for producing the composite papyraceous material according to Claim 10, wherein the papermaking method is a wet papermaking method.

- 12. (Original) The method for producing the composite papyraceous material according to Claim 11, wherein the papermaking method include a dispersion step of dispersing a fibrous polytetrafluoroethylene, a mixing step of mixing a fibrous polyimide, a papermaking step, a pressurization step, and a drying step.
- 13. (Original) The method for producing the composite papyraceous material according to Claim 12, additionally including a heat-pressurizing step after the drying step.
- 14. (Currently amended) The composite papyraceous material according to any one of Claims 1 to 9 Claim 1, for used as any one selected from the group consisting of seamless belt, circuit board, stamping mold, filter, guard tube, flame-resistant paper material, solder pattern paper, papyraceous material for polishing, electrolyte film, lubricant member, sealing member and cushioning material.